

# RCL-50B



## 80,000 CD Remote Controlled Searchlight Product No. 1939.3 (12V)



- > Internal elevation mechanism provides pitch control of spotlight beam; protects elevation mechanism from weather
  - > Includes fingertip remote control Point Pad™; up to three remote Point Pad™ units may be installed on system; surface/flush mount options included
  - > XRCiZ™ feature rotates and moves light assembly every 30 days from activation to keep all bearing surfaces free of corrosion and all electrical contacts functional (can be disabled)
  - > Salt water-resistant construction with nylon and phenolic washers, aluminized stainless steel screws with insulating lubricant
- > Wiring harness 12 ft (3.65 m) length
- > Application: Small to mid-size pleasure, small commercial crafts

<b>Size:</b>	8.4 x 6.0 x 8.0 in (21.3 x 15.2 x 20.3 cm); 4.75 in (120.7 mm) diameter
<b>Weight:</b>	6.2 lbs (2.8 kg)
<b>Material:</b>	Aluminum
<b>Color:</b>	White
<b>Operation:</b>	Remote controlled Point Pad™
<b>Beam Angle:</b>	7°
<b>Elevation Angle:</b>	20° up, 20° down
<b>Rotation:</b>	360° continuous
<b>Rotation Speed:</b>	15° per second,
<b>Elevation Speed:</b>	6° per second (12VDC)
<b>Lamp:</b>	High intensity 55W Halogen
<b>Accessories:</b>	Secondary Point Pad™ for remote control with install kit (P/N 9282.3) Replacement Halogen Lamps: 55W/12V (P/N 6002)
<b>Limited Warranty:</b>	1 Year
<b>Carton Dimensions:</b>	12.5 x 8.0 x 11.5 in (32 x 20 x 29 cm)
<b>Carton Weight:</b>	9 lbs (4.0 kg)
<b>Units Per Carton:</b>	1



ACR Electronics, Inc.  
5757 Ravenswood Road  
Fort Lauderdale, FL 33312, U.S.A.  
Tel Worldwide: +1(954) 981-3333  
Fax: +1(954) 983-5087  
[www.acrelectronics.com](http://www.acrelectronics.com)